

## Microwax HP-500

Microwax HP-500 is a blend of various waxes selected from hydrocarbon family. They exhibit good gelling property and provide good barrier to moisture. It finds application in textiles, automobiles, rubber, tyres, rust preventive sealants and precision metal castings etc.

---

### Typical properties:

Property	Test Method	Value
Appearance	Visual	Slab form
Color	ASTM D-1500	1- 4
Drop melting point( <sup>0</sup> C)	ASTM D-127	80-85*
Flash point ( <sup>0</sup> C)	ASTM D-92	220 min.
Needle penetration at 25 <sup>0</sup> C	IP-376	25-50
Kinematic viscosity at 100 <sup>0</sup> C	ASTM D-445	15-25

\* Product with higher drop melting point of 88-94<sup>0</sup>C can be supplied, if desired by customer.

---

### Product form and packing size:

Product is manufactured in the Slab form and packed in 27.5 kgs bags/cartons.

---

The information provided herein is believed to be reliable; however, no guarantees are made or liability assumed.

66/67, Nariman Bhavan, Nariman Point, Mumbai – 400021 India Tel.: +91-22-2288 3061-64 Fax: +91-22-2202 9364

[www.savita.com](http://www.savita.com) SAVSOL | TRANSOL